

FitNets: An Adaptive Framework to Learn Accurate Traffic Distributions

Alexander Dietmüller
ETH Zürich

Albert Gran Alcoz
ETH Zürich

Laurent Vanbever
ETH Zürich

Abstract

Learning precise distributions of traffic features (e.g., burst sizes, packet inter-arrival time) is still a largely unsolved problem despite being critical for management tasks such as capacity planning or anomaly detection. A key limitation nowadays is the lack of feedback between the control plane and the data plane. Programmable data planes offer the opportunity to create systems that let data- and control plane to work together, compensating their respective shortcomings.

We present FitNets, an adaptive network monitoring system leveraging feedback between the data- and the control plane to learn accurate traffic distributions. In the control plane, FitNets relies on Kernel Density Estimators which allow to provably learn distributions of any shape. In the data plane, FitNets tests the accuracy of the learned distributions while dynamically adapting data collection to the observed distribution fitness, prioritizing under-fitted features.

We have implemented FitNets in Python and P4 (including on commercially available programmable switches) and tested it on real and synthetic traffic traces. FitNets is practical: it is able to estimate hundreds of distributions from up to 60 millions samples per second, while providing accurate error estimates and adapting to complex traffic patterns.

1 Introduction

Collecting reliable traffic statistics is one of the most fundamental problems of network monitoring and is crucial for successfully operating a network. Traffic statistics (i.e., traffic distributions) are indeed used in a wide range of network management tasks including capacity planning, traffic engineering, billing, and fault-detection.

Despite its importance, collecting such statistics remains a challenge, in particular in Internet Service Providers (ISPs). As ISPs do not have control over the end hosts, operators have no choice but to collect traffic statistics using suboptimal in-network monitoring tools. Typical example of such monitoring tools include NetFlow [6] and sFlow [15]. As both

such tools are based on random packet sampling, their outputs typically only cover a very small fraction of the network traffic, and quite poorly so. Studies have shown that simple packet sampling strategies (e.g., 1 in N) fail to estimate key statistics such as the distribution of flow sizes [7, 17].

With programmable networking devices using languages such as P4 [4], new approaches to network monitoring have emerged in an attempt to cast off the drawbacks of packet sampling by getting “closer to the information”, moving processing to the data plane. The two most prominent advances in this direction are: (i) processing *queries* by executing operations such as *filter* and *map* on all the traffic, returning only the result to the control plane [9, 13]; and (ii) aggregating frequency statistics using *sketches*, probabilistic data structures from which the control-plane can extract information approximately (e.g. e.g. [12, 20]). However, both approaches are fundamentally limited by the capabilities of programmable data-planes, which support only simple instructions and limited memory access in order to process traffic at line rate.

To sum up, a gap remains between sampling-based solutions, in which a powerful control plane acts on sparse information, and sampling-free solutions, which are limited by the capabilities of programmable data-planes.

FitNets This paper presents FitNets, an adaptive approach and a system which bridges this gap. FitNets combines monitoring in both data- and control plane through feedback. More specifically, FitNets uses the computational power of the control plane to estimate distributions, and the line rate processing capabilities of the data plane to evaluate the accuracy of the learned distributions. Intuitively, this division represents the fact that learning is complex (i.e., has to be done in software), but verifying it is easy (i.e., can be done in hardware).

Similarly to *active learning*, FitNets control plane optimizes sampling to collect information where it is needed most to improve the estimates. This flexibility in adapting the sampling rate enables FitNets to meet a wide range of management objectives. Among others, it can *minimize* the required




Figure 1: FitNets learns from traffic to optimize monitoring.

sampling rate while maintaining fixed accuracy requirements, and on the other hand, FitNets can *maximize* the accuracy (in a max-min approach) for fixed sampling rates. We want to note that FitNets is not limited to these two approaches and can easily be extended to arbitrary adaptation strategies.

We have fully implemented FitNets including its control plane (in Python) and its data plane components (in P4, including with support for commercially available programmable switches). Our evaluation using real and synthetic traffic traces shows that FitNets is practical: It is able to estimate hundreds of distributions from up to 60 millions samples per second, while providing reliable accuracy estimates and adapting to complex traffic patterns.

2 Overview

In this section, we provide an overview of FitNets using a motivating example. FitNets’ pipeline consists of four main connected steps (see Figure 1): (i) estimating distributions from samples (control plane); (ii) scoring estimates on *all traffic* (data plane); (iii) normalizing the the scores to reliably estimate the current accuracy (control plane); and (iv) adapting the sampling to operator goals (control plane).

Example Alice and Bob are operators responsible for network monitoring of two internet service providers, *A*, and *B*. Both have a set of *monitoring tasks*: They have defined (i) where they want to collect data, i.e. sample traffic; (ii) which parts of traffic they are interested in, e.g. certain prefixes; and (iii) which statistics they are interested in, e.g. the duration of

traffic bursts, or the time packets spend in queues. While their tasks are similar, their demands are different:

- *A* wants to ensure smooth operation while minimizing cost. The monitoring tasks need to meet a certain level of accuracy, while requiring as little sampling as possible.
- *B* wants to invest in network research and is consequently interested in high accuracy across all tasks. However, the network needs remain operational, and there is a hard limit on the available bandwidth.

Despite their different goals, both *A* and *B* ultimately try to determine the optimal sampling rate across different tasks.

A naive monitoring system that returns only the raw sampled data lacks information on the accuracy of statistics that can be extracted. Typically, only a few percent of network traffic can be realistically monitored, and attempting to estimate the accuracy based on only this fraction of traffic potentially misses the majority of information, e.g. over-estimating how well a statistic represents traffic, because it fits the small sample well. To make matters worse, network statistics typically both vary greatly in their complexity as well as may change over time, which makes manual analysis infeasible, as by the time the operator has evaluated the estimate, the underlying traffic has likely changed already.


Consequently, both Alice and Bob end up either sampling too much or too little traffic for the respective statistics. *A* resorts to over-provisioning to ensure that the minimum accuracy requirements are met, resulting in unnecessary cost, while *B* tries to manually adjust the sampling for each task, and is prone to miss new trends or react slowly..

FitNets provides an adaptive framework addressing both Alice’s and Bob’s problems. It is based on two core concepts:

Learning FitNets does not only return raw data to the operator. Instead, it deeply integrates estimating the required statistics from the data, and uses programmable data planes to estimate the accuracy of the learned statistics on all network traffic.

Adaptation FitNets offers programmable adaptation. It can be programmed to automatically adapt sampling to meet operator-specified goals.

Concretely, *A* and *B* first specify their respective monitoring tasks using a simple query language (which we introduce in section 4) and configure the adaptation objective. *A*’s objective corresponds to minimizing the sampling rate for given accuracy requirements, while *B*’s objective corresponds to maximizing the accuracy for a given bandwidth. Both objectives are supported by FitNets. Consequently, FitNets enables monitoring that adapts to operator-specified requirements in the face of complex and changing network statistics.



(a) The KDE is a sum of kernels centered at samples. (b) A higher bandwidth (wider kernels) smooths the estimate.

Figure 2: Kernel Density Estimation

3 Estimation of Traffic Distributions

Estimating traffic distributions and providing both reliable as well as comparable accuracy scores are the core concepts that allow FitNets to produce a stream of probability distributions that can be used effectively, e.g., to optimize sampling or to enable operators to make informed decisions based on the observed accuracy of estimation. In summary, FitNets’ estimation goes through three steps:

Estimation The distributions of features are estimated from samples using *Kernel Density Estimation* (section 3.1).

Scoring The estimates are scored using *proper scoring rules*, which can be computed in the data plane (section 3.2).

Normalization The accuracy of estimates is computed by normalizing the score, which requires FitNets to estimate the (unknown) optimal possible score (section 3.3).

This allows FitNets to return distributions for arbitrary traffic features, along with normalized scores, which are comparable even for different distributions. Additionally, the low complexity of score computation enables data-plane scoring.

3.1 Kernel Density Estimation

Estimating distributions for network traffic features is challenging, as the underlying distributions can have complex shapes (e.g., assumptions such as normality do not necessarily hold) and may change over time. Furthermore, to cope with the large volume and dynamic nature of network traffic, the estimates must be both efficient and fast to compute.

In this setting, Kernel Density Estimators (KDEs) are useful non-parametric estimators, which do not assume any shape of the underlying distribution and can be efficiently computed using the fast Fourier transformation (FFT) [18, p. 183]. Additionally, the mean integrated square error (MISE) of a KDE can be asymptotically approximated for a given training sample size, even if the true distribution is unknown.

Density Estimation A KDE estimates a distribution by combining *kernels*, which are centered at each sample and scaled by a *bandwidth*, which results in a ‘smoothed line’ through the data points (shown in figure 2a with gaussian kernels). The kernel function mainly determines the mathematical properties of the resulting estimate, such as differentiability, while the bandwidth determines the trade-off between bias and smoothness (figure 2b). As evident in the definition, KDEs require *no* assumption about the underlying structure of the data, such as normality, and belong to the class of non-parametric estimators.

Formally, let x_1, \dots, x_n be independent and identically distributed samples from an unknown probability density f . The KDE f_n is defined as [18, p. 11]:

$$f_n(x) = \frac{1}{nh} \sum_{i=1}^n K\left(\frac{x-x_i}{h}\right) \quad (1)$$

Here, K is the *kernel* (s.t. $\int K(x) dx = 1$) and h is the *bandwidth* of the estimator.

Asymptotic Convergence KDEs are asymptotically unbiased, i.e., given sufficient samples, they can estimate any distribution in the sense that the *Mean Integrated Square Error* (MISE), which is defined as

$$\text{MISE}(f_n) = \text{E} \int (f_n(x) - f(x))^2 dx \quad (2)$$

goes to zero for $n \rightarrow \infty$ [18, p. 23]. The Expectation is taken over all possible training samples of size n drawn from f .

In particular, for optimal bandwidth, the MISE can be asymptotically approximated for large sample sizes by

$$\text{MISE}(f_n) \approx cn^{-4/5} \quad (3)$$

where the constant factor $c > 0$ depends mainly on $|f''|$, i.e. the curvature of the unknown distribution [18, p. 22]. It also depends on the shape of the kernel function, yet the difference between commonly used kernel functions is small [18, p. 31].

Optimal Estimation The bandwidth for optimal asymptotic convergence depends on the unknown true distribution f (on $|f''|$, to be precise), and it is subsequently impossible to pick the optimal bandwidth, and thus the optimal estimator, a-priori. However, the optimal bandwidth can be approximated.

Several rules to approximate the optimal bandwidth exist, from simply trying multiple candidates and selecting the best via cross-validation, to more sophisticated approaches that try to estimate f'' in order to compute the optimal bandwidth. While KDEs themselves are non-parametric, some of these selection rules require assumptions such as normality and are not suitable for our situation.

In order to remain non-parametric, we use an algorithm known as the ‘*Improved Sheather-Jones Algorithm*’ [5], which

estimates the optimal bandwidth over a series of iterations and does not require normality or other assumptions on the shape of the distribution. In particular, it is robust (in the sense that it can find a good bandwidth even for difficult distributions) and can be efficiently computed.

3.2 Proper Scoring Rules

As the true distribution is unknown, it is impossible to determine the exact error of an estimated distribution. However, it is possible to score the estimate with a test sample. If the score is computed according to a *proper scoring rule* [8], it is closely related to a distance measure, in the sense that maximizing the score minimizes the distance between the estimated and true distribution. In particular, FitNets uses the so called *Quadratic Score* (QS), which is a proper scoring rule. The distance measure associated with the QS is the *Integrated Square Error* (ISE), maximizing the QS minimizes the ISE.

Propriety A scoring rule is *proper*, if it ‘rewards the best estimate’. Let f_n be an estimated distribution and x a test sample. The score $S(f_n, x)$ assigns a real-valued score to observing x for the estimated distribution. The score is usually computed with more than a single test value; let $S(f_n, f)$ denote the expected score w.r.t. test values x drawn from f . The scoring rule is called *proper*, if the correct estimate achieves the highest score (in expectation), and *strictly proper*, if *only* the correct prediction achieves the highest score. Formally, a rule is proper, if $S(f, f) \geq S(f_n, f) \forall f_n, f$ and strictly proper, if this holds with equality if and only if $f_n = f$ [8].

Distance Proper scoring rules have an associated distance measure, which is the difference between the optimal score, i.e. the score of the true distribution f , and the score of the estimated distribution f_n [8]:


$$d(f_n, f) = S(f, f) - S(f_n, f) \quad (4)$$

Quadratic Score The quadratic score is defined as [8]:

$$QS(f_n, x) = \underbrace{2f_n(x)}_{\text{reward}} - \underbrace{\int f_n(\omega)^2 d\omega}_{\text{regularization}} \quad (5)$$

and as indicated above, it can be interpreted as combination of a reward for predicting the correct probability of a test sample and a regularization term, penalizing overly complex estimates (independent of the test sample). It’s associated distance measure is the integrated square error:

$$d(f_n, f) = QS(f, f) - QS(f_n, f) = \int (f_n(x) - f(x))^2 dx \quad (6)$$



(a) Two exemplary scores. (b) The same scores, normalized.

Figure 3: Normalization makes performance comparable.

And in expectation with respect to the sample from which f_n is formed, the MISE is thus related to the distance taken with the expected score of f_n :

$$MISE(f_n) = QS(f, f) - E[QS(f_n, f)] \quad (7)$$

Data Plane Scoring Given a density estimate f_n , computing the score $QS(f_n, x)$ for x in a test sample can be done in a single pass over the test sample, and can be computed in the data plane. Concretely, computing the mean consists first looking up the reward, i.e. the estimated probability $f_n(x)$, for each incoming value x , and subsequently incrementing counters for both the number of samples and sum of rewards, in order to allow computation of the mean. The regularization on the other hand is unrelated to the test sample and can be computed from the density estimate alone.

3.3 Normalization

Scores for estimated densities of different distributions need to be *normalized*, otherwise they are not comparable. However, normalization is not trivial and requires estimation of the optimal achievable score. FitNets uses a series of observed scores to compute an approximate normalization. Concretely, we formulate this approximation as a constrained linear optimization problem, which can be efficiently solved. After normalization, scores can be interpreted as an *estimation accuracy*, which is 1 for the optimal estimate, and lower otherwise. Additionally, the the solution of the optimization problem can be used to *predict* the required sample size to reach a certain accuracy, and vice versa the expected accuracy given a certain sample size, which enables the sampling rate adaptation of FitNets.

Comparability requires Normalization Proper scoring rules combine the ‘predictability’ of a distribution with the quality of the estimate, and thus they need to be handled carefully when comparing scores of different distributions [8]. Concretely, a particular score might be close to optimal for one distribution, but far off for another. Thus, we propose

normalizing the score by the optimal score, such that a score of 1 always represents the optimal estimate, regardless of the true distribution (figure 3):

$$\text{NS}(f_n) = \frac{S(f_n, f)}{S(f, f)} \quad (8)$$

Accordingly, we define the *normalized quadratic score* as $NQS(f_n) = QS(f_n, f)/QS(f, f)$. We note that a normalized (strictly) proper score is still a (strictly) proper score, propriety is conserved under affine transformations [8].

Normalization requires the optimal score $S(f, f)$, which cannot be computed exactly without the (unknown) true distribution and can only be approximated.

Approximate Normalization We can approximate the optimal score for KDEs scored using the quadratic score. Above, we have shown that the expected distance associated with the quadratic score is the MISE (equation 7), which can be asymptotically approximated for KDEs (equation 3):

$$\text{QS}(f, f) - E[\text{QS}(f_n, f)] \approx cn^{-4/5} \quad (9)$$

The unknown quantities in equation 9 are c and $\text{QS}(f, f)$, which both rely on the unknown true distribution. The remaining terms, i.e. the training sample size and expected score for this size, can be empirically measured and subsequently, equation 9 can be solved for an approximate optimal score.

Constrained Linear Optimization An approximate optimal score can be computed by solving a linear optimization problem. Concretely, let \vec{N} be a vector of distinct samples sizes, and let \vec{S} be a vector of mean quadratic scores, s.t. \vec{S}_i is the mean score of distributions estimated from samples of size \vec{N}_i from f . Then, we estimate the optimal score by solving the following linear optimization problem:

$$\min_{\text{QS}_{opt}, c} \quad \|\vec{I} \cdot \text{QS}_{opt} - \vec{S} - c\vec{N}^{-4/5}\| \quad (10)$$

$$\text{subject to} \quad \begin{bmatrix} \text{QS}_{opt} \\ c \end{bmatrix} \geq \begin{bmatrix} \text{QS}_{max} \\ 0 \end{bmatrix} \quad (11)$$

where $\text{QS}_{opt} = \text{QS}(f, f)$ and QS_{max} is the highest score observed for all estimates for the distribution.

Regarding the constraints, the constant c is by definition positive; and as the quadratic score is proper, the optimal score must be as least as large as any observed score.

Prediction With the solution of the optimization problem we can both predict the normalized score for a given sampling size, as well as the expected sample size required to reach a score. Concretely, the predicted normalized quadratic score for a sample size n is:

$$\text{QS}_{pred}(n) = 1 - \frac{c}{\text{QS}_{opt}} n^{-4/5} \quad (12)$$

This function is invertible, and the inverse predicts the required sample size for a given score.

Task	Location	Constraints	Feature
1	Switch 1	src(42.0.0.0/8)	burst_size
2			burst_duration
3		src(43.0.0.0/8)	queue_time
4	Switch 2	src(13.37.0.0/16) & proto(TCP)	packet_size
⋮			⋮

Figure 4: Monitoring tasks define *where* to monitor *which* feature under *which* constraints on the traffic.

Practical Improvements Repeatedly drawing samples, estimating distributions, and scoring them, in order to compute the mean score for multiple sample sizes, is impractical in practice. By using sub-sampling, the required data points for normalization can be acquired in parallel to the density estimate which is supposed to be normalized.

Let S be a sample of size n , and f_n be the KDE computed from S . In order to report f_n to the operator, we need a normalized score for f_n . We employ the following strategy. First, select a number of range of sample sizes $n_i < n$ and draw respectively sized sub-samples S_i from S . In parallel to the estimation of f_n , estimate additional densities f_{n_i} . Second, score f_n and all additional estimates in parallel, which results in the required data points to solve the optimization problem and normalize the score for f_n without additional steps.

Generalization Above, we use the established theory of KDEs combined with quadratic scores to form a linear optimization problem. However, we argue that this approach can also be generalized to other kinds of estimators and scoring functions under the assumption that the expected distance of an estimate decreases with increasing sample size, albeit with unknown rate. This results in a nonlinear optimization problem similar to 10, which requires more resources to solve, yet demonstrates that the feasibility of our estimation is not limited to KDEs and quadratic scoring rules (Appendix A.1).

4 System Design

FitNets consists of four main components, (i) (adjustable) sampling; (ii) density estimation; (iii) evaluating the estimated densities; and (iv) optimizing the sampling rate for each task.

In this section, we explain the concrete design of FitNets from the top down, first we define the inputs FitNets requires from the operator, and what it returns (section 4.1); next, we explain estimation, optimization, and adaptation, in the control plane (section 4.2); and finally, we analyze the data plane processing pipeline (section 4.3).

4.1 Interface

As introduced in section 2, operators configure FitNets with a list of monitoring tasks and an adaptation objective. In return, FitNets provides a stream of estimated probability distributions, along their accuracy, for each monitoring task.

Input: Monitoring Tasks Monitoring tasks are specified by (i) the *location*, i.e. the programmable switch, where traffic is monitored; (ii) *constraints*, i.e., which traffic is monitored; and (iii) which *features* are monitored. For each location, multiple constraints can be specified, and similarly, for each constraint, multiple features can be monitored. Figure 4 shows a set of exemplary tasks. FitNets supports a set of commonly used constraints and features, which we discuss in the following. However, we want to note that in general, FitNets is compatible with any constraint that can be matched on programmable network devices, as well as any feature that can be extracted.

For *constraints*, we have implemented the five tuple of source address, destination address, protocol, source port and destination port, either individually or in combination, as they are the most common way to distinguish network traffic.

For *features*, we have implemented a selection of simple features that can be directly extracted from a single packet, e.g. packet size, as well as more complex features that require state between packets, such as inter-arrival time of packets and the duration of flowlets (short burst of packets, separated by a gap of inactivity). We focus on traffic bursts as they are both valuable for network monitoring, and only need to stay in memory for a short time. Consequently the number of concurrently active flowlets for common timeouts such as 100 – 500ms is typically well below 100k, which is feasible on programmable network devices (e.g. [3]). Features that require state for *flows* are a greater challenge. As flows can be active for minutes, millions of them are typically active at the same time. Solving this challenge is out of scope for this paper, yet we argue that it is orthogonal to FitNets. Any method developed to efficiently handle flow state on programmable network devices, in software or hardware, immediately extends the range of feature supported by FitNets.

Input: Adaptation Objective Currently, FitNets supports two common adaptation objectives, either (i) maximizing the accuracy across all tasks for fixed resources; or (ii) minimizing the resources for a fixed accuracy. If needed, it can be easily extended to adapt for other operator defined objectives.

Output: Scored Densities FitNets processes incoming data in steps, e.g. every second. After each step, it returns a density estimate for each monitoring task, along with its accuracy.




Figure 5: In the control plane, FitNets estimates density and solves the linear optimization problem to compute their accuracy. Additionally, it optimizes the sampling rate.

4.2 Control Plane

At each computation step, the control plane, (i) estimates densities; (ii) normalizes scores; and (iii) adapts the sampling rate per task (figure 5). Over multiple steps, this forms the following monitoring pipeline:

Estimation At step i , density models are estimated from samples collected since step $i - 1$. The estimated densities are sent back to the data plane for scoring.

Normalization At step i , FitNets receives the scores for densities estimated at step $i - 1$. FitNets solves the optimization problem required to normalize scores.

Adaptation Finally, FitNets adapts the sampling rate per task, optimizing the objective selected by the operator.

In the following, we describe all three steps in further detail, and highlight how FitNets scales through parallelization.

Estimation FitNets needs to estimate multiple densities per task; one density from all the available data, to be returned to the operator, and additional densities from subsamples, to enable score normalization to compute the accuracy.

It is possible to re-use a sample to estimate additional densities by drawing multiple subsamples (section 3.3). FitNets employs a simple sub-sampling scheme of repeatedly splitting the original sample into evenly sized subsamples, e.g. two subsamples consisting each of a random half of the original sample, three subsamples consisting of a third, and so on. This strategy ensures that for each subsample size, we use all available data, but do not use data points multiple times, which could bias the density estimate and thus the mean score.

Regardless of how many densities are estimated, FitNets only sends a single ‘mean density’ per task and sample size to the data plane. The mean of multiple quadratic scores is the mean of rewards minus the mean of regularization. Thus, instead of scoring each single model and computing the mean of scores, FitNets first computes a single mean density, and sends only this mean estimate to the data plane for scoring.

Normalization From scores received by the data plane, combined with the corresponding sample sizes from estimation, FitNets approximates the optimal score per task (as explained in section 3.3). Concretely, FitNets uses a constrained least squares solver. The optimal score is subsequently used to normalize the score of density estimated from the complete sample, which can subsequently be returned to the operator.

Adaptation FitNets uses the ability to predict scores to adapt the sampling rate for each task. After solving the normalization problem, we can estimate the expected normalized score (i.e. accuracy) for a given sample size n (section 3.3). This allows FitNets to optimize both adaptation objectives:

Resource Minimization FitNets predicts the required resources to reach the operator-specified accuracy for each task and adapts the sampling rate to collect exactly this (minimal) amount of required resources.

Accuracy Maximization FitNets optimizes the *max-min* accuracy across all monitoring tasks, i.e. it ensures that the accuracy for the least accurate density is maximized, to improve across all tasks. For any given accuracy, FitNets predicts the total resources required. Subsequently, finding the specific accuracy that uses all available resources, but not more, is a scalar root-finding problem.

Scalability The control plane of FitNets scales to large number of simultaneous tasks, as most processing steps are independent. For *each task*, the density estimates for different samples can be computed in parallel, and parallel to the score normalization. *Multiple tasks* can not only be parallelized, but also distributed across multiple machines, as the processing for each task relies only on the samples and scores for this particular task. The parallelization of adaptation depends on the objective. For resource minimization, the individual tasks are independent and consequently, the adaptation can also be parallelized. Accuracy Maximization on the other hand cannot, as the maximal accuracy depends on the required resources of any individual task (this affects *only* adaptation, estimation and normalization can still be parallelized).

4.3 Data-Plane

Conceptually, the data-plane processing consists of three steps, (i) preprocessing, i.e. matching traffic and extracting features; (ii) sampling; and (iii) scoring (figure 6).

In the following, we first summarize the general architecture of programmable network devices, and next take a closer look at the three data-plane processing steps.

Architecture Programmable switches, programmed using languages such as P4 [4] process packets with a multi-stage pipeline. In each stage, one or more match-action tables(s) are applied, which can read and modify both packet headers and additional per-packet metadata. Additionally, a table can also access objects persisting state between packets, such as device registers or rate-limiting meters.

A P4 program may be separated into its architecture and configuration. The architecture defines the control-flow of the program, e.g. table layout or memory type and size. Changes to the architecture require re-compilation of the program, and typically a restart of the switch in order to install the new architecture. The configuration includes table rules, memory content, and meter rates, and can be changed at runtime.

The monitoring tasks determine the data-plane architecture of FitNets. During setup, the pre- and post-processing steps are programmed and the required memory for flowlet state and scores is allocated, and meters for each task are instantiated. Changes to the monitoring tasks require changes in memory, in particular for scoring memory, and consequently a recompilation of the program.

Preprocessing First, FitNets extract features from traffic matching the constraints specified in the monitoring tasks. For the constraints, FitNets employs a table matching on the 5-tuple of packet and returning the id of all active monitoring tasks. A monitoring task is active, if its constraint matches. The table uses ternary matches, which allow flexible queries such as ranges, longest-prefix-match, covering even complex constraints such as ‘UDP packets from the subnet 42.0.0.0/8 with a destination port below 1024’. Additionally, FitNets checks whether any task requires flowlet state.

If flowlet state is required, FitNets checks the *flowlet state* of the current packet using a hash table. The flowlet state can be either (i) the packet is the start of a new flowlet; (ii) the packet belongs to an active flowlet; (iii) the packet ends a flowlet (e.g. after a TCP FIN); or (iv) the state could not be determined because of a hash collision.¹ Concretely, FitNets stores the flow id and the timestamp of the last packet of the flowlet to both check for collisions and timeouts.

Finally, FitNets extracts the features of active tasks. For each separate feature, FitNets keeps a table that matches on the active tasks.² Additionally, flowlet features might keep further state, e.g. a byte counter for flowlet sizes. FitNets cannot extract every feature after every packet, e.g. the flowlet duration can only be returned for the last packet, and excludes un-extracted features from sampling and scoring.

¹FitNets keeps a collision counter such that operators can adjust the flowlet state size, as memory cannot be resized at runtime.

²Flowlet feature only match if there has *not* been a collision




Figure 6: The FitNets data plane first matches traffic and extract features (preprocessing), then either samples the feature or uses it for scoring. Multiple features can be processed in parallel, for simplicity, only a single one is shown. During preprocessing, flowlet feature require state; to conserve memory, FitNets shares flowlet state between features as much as possible.

Sampling For each task, FitNets individually decides whether the feature is sampled or used for scoring via rate-limiting meters configured from the control plane. We use ‘direct meters’ attached to the feature extraction tables. Direct meters keep individual rates for each match of the table and are automatically executed whenever the table matches. At runtime, the control plane configures the rates of the individual matches of the feature extraction tables, i.e. of the monitoring tasks, as each tasks corresponds to a feature. Consequently, in the same stage in which features are extracted, the direct meter output marks the feature for either ‘sampling’ (within the specified rate) or ‘scoring’ (above the rate).

Finally, FitNets creates a new packet containing tuples of (task id, feature value) for all features marked for sampling, and sends it to the control plane.

Scoring In the final step of the data-plane pipeline, FitNets uses unsampled feature values as test samples to update the estimation scores for the respective tasks.

As described in section 3, FitNets requires two counters per density estimate, one for the number of test samples, and one for the sum of rewards (the sum of $f_n(x)$ for all test samples x). For multiple estimates (from multiple training sample sizes), FitNets can share the counter for the number of test samples, and thus needs to keep $k + 1$ counters to score densities estimates from k distinct sample sizes (per task).

In particular, FitNets implements the lookup of $f_n(x)$ using ternary matches. This allows us to keep the number of table entries constant, while dynamically adjusting the resolution to the range of f_n (we provide further detail in appendix A.2).

5 Evaluation

In this section we show that FitNets is accurate for distributions representative for real network traffic, scales, and is implementable on programmable network devices.

In particular, we analyze: the flexibility of KDEs to learn arbitrary distributions (section 5.2), how data-plane scoring ensures reliable scores (section 5.3), and that the accuracy of estimates is approximated with an error below 5% (section 5.4). Furthermore, we evaluate FitNets’s scalability in terms of concurrent estimates and samples per second for density estimation and in terms of computation time for the accuracy approximation (section 5.5). Finally, we present the two adaptation modes of FitNets in case studies (section 5.6).

5.1 Methodology

Ground Truth In order to evaluate the performance of FitNets, in particular the accuracy of score normalization, we require ground truth distributions. Thus, we extracted representative distributions for each feature FitNets from real-world network traces. We analyzed one hour of the CAIDA backbone traces [2] and collected data for five different traffic features monitored by FitNets. For all features that require flowlet state, we have chosen an inter-packet gap of 500ms, i.e. after a time gap of 500ms, a flowlet is considered over.

We have used KDEs to estimate probability distributions for each feature (figure 7) from the observed feature values, which we use as ground truth for our evaluation. The five distributions show both a broad range of shapes, e.g. the size distribution is bimodal (figure 7a), showing a large peak for very small packets, and a smaller peak for packets at maximum frame size, with other sizes mixed in between. The distribution for the observed floatlet durations shows an even more complex shape (figure 7e). Furthermore, the distributions also exhibit largely different scales, from tens of milliseconds for inter-arrival time to hundred-thousands of bytes per burst. We argue that this diversity is typical for network traffic. While the used distributions are *representative*, we want to stress that the distributions represent just a moment in time. In different networks, the same features are likely distributed differently.




Figure 7: We evaluate FitNets with five probability densities representative for features observed in real network traces. The distributions feature a broad range of shapes and scales, ranging from tens of milliseconds, to hundred-thousands of bytes.

With the distribution, we can in particular determine (i) the expected score of an estimated density, useful for comparison with empirical scores from test samples; (ii) the optimal score; (iii) the accuracy or normalized score by dividing the expected score by the optimal score; and (iv) the integrated square error (ISE) between an estimate and the true distribution.

Implementation We have implemented a multi-core version of the FitNets control plane in roughly 1000 lines of Python code (using frameworks for KDE [14] and optimization [11]). We process packets using a simulated switch, i.e. our simulator runs data- and control-plane on a single machine. In addition, we have implemented the P4 version of the FitNets data plane in P4₁₄, P4₁₆ and P4_{Tofino} (for the Intel Tofino Switch [1]) in roughly 500 lines of P4 code each.

5.2 Density Estimation

KDEs can approximate any distribution asymptotically for increasing training sample size, but some distributions require a large sample size than others (figure 8). In this experiment, we evaluate how KDEs estimate different distributions by repeatedly drawing samples of increasing size from the each distribution, computing the KDE, and evaluating the ISE between the estimated and true distribution. The figure shows the average ISE along with the standard deviation across 100 repetitions per distribution and sample size. As evident, the error approaches 0 for all all distributions, as for all distributions, the ISE steadily decreases with n , while some distributions are harder to estimate than others. For example, reaching an ISE below 10^{-4} requires $100k$ samples for the inter-arrival time, and less than 1000 samples for the flowlet duration.

5.3 Data-Plane Scoring

Only test samples at about as large as the training sample lead to reliable ($< 10\%$ error) scores (figure 9) across all evaluated features. In this experiment, we repeatedly train KDEs and

score each KDE with test samples of varying size, to compare the empirical scores to the true score of the estimate.

We pick training samples of varying size and determine the test sample size in relation to the training sample, ranging from $0.1 \times$ to $100 \times$ the training sample size. This reflects typical training situations, e.g. a data scientist usually reserves a fraction of the data for testing, e.g. 20%; or in the case of FitNets, 1% of network traffic might be sampled and used for estimation, and subsequently 99% for testing.

The figure shows the mean score accuracy for a given ratio of train to test sample size, along with the standard deviation, over 100 repetitions for each distribution, train-, and test sample size. The results for the individual training sample sizes are comparable, thus we only show the results aggregated over all training sample sizes. For test samples smaller than the training sample, the error between the empirical score and true score varies strongly, and in cases goes up to 40%. For test sample at least as big as the training sample, the error is below 10% in most cases, and for even larger test samples, the error decreases further, approaching 0% for all distributions.

This highlights one of the benefits of benefits of data-plane scoring: FitNets does not need to reserve a large fraction of the sampled data to compute reliable scores. Instead, it profit from typically low sampling rates, as this ensures that a large number of samples is used for scoring in the data-plane, resulting in reliable scores.

5.4 Normalization

FitNets approximates the estimation accuracy with low error with only a few additional density estimates (figure 10).

FitNets approximates the estimation accuracy by approximating the optimal achievable score from additional density estimates, trained with sub-samples of the training sample (section 4.2). In this experiment, we analyze the estimation accuracy, i.e. how well the returned accuracy matches the true accuracy, depending on the number of density estimates.




Figure 8: KDEs can approximate all distributions asymptotically, but some require a larger sample to be estimated well.




Figure 9: A low relative error in of the empirical score requires a large testing sample.




Figure 10: Even with only few estimators, the accuracy is approximated with an error below 5%.

The approximation error across 100 repetitions is below 15% for 2 additional estimates, and below 5% for 5 additional estimates. Our experiments indicate that using a larger number of distinct sample sizes with our subsampling strategy does not substantially improve the performance further, as the the training sample is split into subsamples of decreasing size, which decreases the quality of the additional estimators. Nevertheless, we argue that an approximation error of below 5% is sufficient in real-life situations.

5.5 Benchmarks

In this section, we analyze the scalability of FitNets by measuring the control-plane execution time. All experiments are repeated 5 times, and we show the mean execution time.

First, we analyze the time needed to compute probability densities from incoming feature samples. FitNets scales well to large sample sizes, and *requires roughly 40 milliseconds to estimate a distribution for up to 100k samples* (figure 11a). For larger sample sizes, the time increases linearly, and requires about 1 second for 3.9M samples. Extending estimation to multiple densities can be efficiently parallelized, as all estimations are independent. On our (16 core) test machine, estimating distributions for 16 densities with 100k samples each requires a bit less than 100 milliseconds (there is some overhead from initializing worker processes and distributing samples). In one second, FitNets can process up to 1.5M samples each for 16 densities in parallel, and a bit short of 100k samples each for 500 densities, which corresponds to 24M and 50M samples in total, highlighting that FitNets can process millions of samples for up to hundreds of densities in parallel on a single machine. As discussed in section 4.2, computation can be further parallelized by distribution across machines, allowing FitNets to scale further.

Next, we analyze the time to solve the optimization problem for normalization, which *requires less than 10 milliseconds per optimization* (figure 11b). As described in section 4.2, solves constrained least squares problem, which takes less than a millisecond to solve, even for a large number of in-

puts. As FitNets does not require many distinct sample sizes to compute an accurate normalization (section 5.4), the computation time of normalization is negligible compared to density estimation requiring less than 50ms for 500 distinct tasks.

5.6 Case Studies: Adaptive Allocation

In this section, we demonstrate both adaptation objectives of FitNets. The first case study addresses resource minimization. We specify an accuracy objective of 0.98 for all traffic features. FitNets is able to keep the required accuracy within ± 0.02 in general, and ± 0.04 in the worst case, while reducing the required samples to a minimum (figure 12)

The second case study addresses accuracy maximization. We specify a fixed bandwidth and compare the performance of FitNets with a static allocation. On average, FitNets achieves higher accuracy with the same total resources (figure 13).

6 Related Work

In-Network Query Processing The processing capabilities of programmable data-planes have given rise to in-network monitoring. In particular, frameworks such as Sonata [9] and Marple [13] provide an interface similar to FitNets: The operator specifies monitoring tasks, in this network queries, consisting of operators such as `filter` and `map`, which are then executed by the network on all traffic, returning results to the operator. While the query language itself is expressive, determining the right query for a given problem can be a complex task in itself, in particular, if the nature of the underlying data is unknown. In contrast, FitNets provides more general information, estimating distributions for specified traffic statistics. FitNets is thus complementing in-network query processing: With the insights gained from the distributions provided by FitNets, network operators can design better network queries.




Figure 11: FitNets is efficient and parallelizable.




Figure 12: FitNets can minimize the sampling resources while maintaining operator specified accuracy goals (here 0.98) with low error.




Figure 13: With a fixed bandwidth, FitNets can achieve a higher accuracy on average than static allocation by adaptively adjusting the sampling rate.

Sketches Sketches, probabilistic counters, e.g. [10, 12, 19, 20], have seen increasing attention as they allow to aggregate data in the network approximately with provable error bounds. In particular, it is possible to estimate traffic distributions from the sketch data structure. However, sketches only apply to *frequency statistics*, i.e. estimating counts. While this makes them well suited to estimate some traffic features, such as the flow size distribution, they are not applicable to others, in particular time-based features, such as the packet inter-arrival time, which FitNets offers. Aside from extracting distributions, the data structure itself is attractive for in-network processing, e.g. used by Sonata to reduce the required memory. As such, they are interesting as a *building block* for FitNets, enabling the extracting of state-intensive features.

Adaptive Stream Processing In the context of video streaming, adapting the bandwidth to meet accuracy objectives has shown to be both feasible and effective [16]. In particular, profiling application accuracy for a given bandwidth (both off- and online) provides a major advance in usability and performance [21]. The adaptation of FitNets builds on the same concepts, i.e. estimating the accuracy and adapting the bandwidth to optimize some objection, on a lower level. In video streaming, estimating the performance of high-level applications can be challenging and time-consuming. We have shown that approximating the accuracy of traffic statistics can be implemented efficiently in programmable data planes based on proper scoring rules.

7 Conclusion

We introduced FitNets, a monitoring approach and system for learning accurate traffic distributions. The key insight behind FitNets is to combine the control plane and the data plane through a feedback loop. In the control plane, FitNets relies on efficient non-parametric models to learn distributions of any shape from sampled data. In the data plane, FitNets tests the accuracy of learned distributions while dynamically adapting data collection. By adapting the sampling rate, we show that FitNets can adapt for a wide variety of monitoring objectives, including matching required accuracy requirements or maximizing accuracy given a fixed sampling budget.

We fully implemented FitNets and show that it can accurately learn representative for real network traffic traces. We confirmed its practicality by implementing it on a programmable network device (Intel Tofino).

A Appendix

A.1 Normalization for Arbitrary Estimators and Scores

The score normalization presented in section 3.3 can be extended to other estimators and/or other proper scoring rules under the assumption that the distance associated with the chosen scoring function can be approximated by some function $d(f_n, f) \approx cn^{-r}$ defined by $c, r > 0$. In other words, we assume that the expected distance of the estimate to the true distribution decreases with increasing sample size, albeit with unknown rate. This gives:

$$cn^{-r} \approx S(f, f) - E[S(f_n, f)] \quad (13)$$

which, using the same notation as for the linear optimization problem, can be formulated as the following nonlinear optimization problem:

$$\min_{c, r, S_{opt}} \|S_{opt} - c\vec{N}^{-r} - \vec{S}\| \quad (14)$$

$$\text{subject to } c, r > 0 \quad (15)$$

$$S_{opt} > S_{max} \quad (16)$$

A.2 Evaluating Probability Densities in the Data-Plane

We implement a binning scheme in order to efficiently manage an unknown range of values for different features. Using exact matches, the number of entries in the lookup table would equal the number of distinct feature values. For features such as the flowlet size in bytes, which can go from 0 to hundreds of thousands, this is infeasible.

Instead, we use bins, with a width of a power of 2, which enables us to fix the number of table rules to a single rule per bin using TCAM matching (e.g. for bins of size 2^3 , we can set the last three bits in the TCAM match to 'ignore'). Furthermore, the size of the bins can be adjusted at runtime, by simply adjusting the matching rules.

References

- [1] Barefoot tofino.
- [2] The CAIDA UCSD anonymized internet traces 2018.
- [3] Mohammad Alizadeh, Tom Edsall, Sarang Dharmapurikar, Ramanan Vaidyanathan, Kevin Chu, Andy Fingerhut, Vinh The Lam, Francis Matus, Rong Pan, Navindra Yadav, and George Varghese. CONGA: Distributed congestion-aware load balancing for datacenters. In *Proceedings of the 2014 ACM Conference on SIGCOMM*, SIGCOMM '14, pages 503–514. ACM. event-place: Chicago, Illinois, USA.
- [4] Pat Bosshart, Dan Daly, Glen Gibb, Martin Izzard, Nick McKeown, Jennifer Rexford, Cole Schlesinger, Dan Talayco, Amin Vahdat, George Varghese, and others. P4: Programming protocol-independent packet processors. 44(3):87–95.
- [5] Z. I. Botev, J. F. Grotowski, and D. P. Kroese. Kernel density estimation via diffusion. 38(5):2916–2957.
- [6] B. Claise. Cisco systems NetFlow services export version 9. Published: Internet Requests for Comments.
- [7] Nick Duffield, Carsten Lund, and Mikkel Thorup. Estimating flow distributions from sampled flow statistics. In *Proceedings of the 2003 conference on Applications, technologies, architectures, and protocols for computer communications*, pages 325–336, 2003.
- [8] Tilmann Gneiting and Adrian E. Raftery. Strictly proper scoring rules, prediction, and estimation. 102(477):359–378.
- [9] Arpit Gupta, Rob Harrison, Ankita Pawar, Rüdiger Birkner, Marco Canini, Nick Feamster, Jennifer Rexford, and Walter Willinger. Sonata: Query-driven network telemetry.
- [10] Qun Huang, Patrick P. C. Lee, and Yungang Bao. Sketchlearn: Relieving user burdens in approximate measurement with automated statistical inference. In *Proceedings of the 2018 Conference of the ACM Special Interest Group on Data Communication*, SIGCOMM '18, pages 576–590. ACM. event-place: Budapest, Hungary.
- [11] Eric Jones, Travis Oliphant, Pearu Peterson, and others. *SciPy: Open source scientific tools for Python*.
- [12] Zaoxing Liu, Antonis Manousis, Gregory Vorsanger, Vyas Sekar, and Vladimir Braverman. One sketch to rule them all: Rethinking network flow monitoring with UnivMon. In *Proceedings of the 2016 ACM SIGCOMM Conference*, SIGCOMM '16, pages 101–114. ACM.
- [13] Srinivas Narayana, Anirudh Sivaraman, Vikram Nathan, Prateesh Goyal, Venkat Arun, Mohammad Alizadeh, Vimalkumar Jeyakumar, and Changhoon Kim. Language-directed hardware design for network performance monitoring. In *Proceedings of the Conference of the ACM Special Interest Group on Data Communication*, pages 85–98. ACM.
- [14] Tommy Odland. tommyod/KDEpy: Kernel density estimation in python.
- [15] P. Phaal, S. Panchen, and N. McKee. InMon corporation's sFlow: A method for monitoring traffic in switched and routed networks. Published: Internet Requests for Comments.
- [16] Ariel Rabkin, Matvey Arye, Siddhartha Sen, Vivek S. Pai, and Michael J. Freedman. Aggregation and degradation in JetStream: Streaming analytics in the wide area. pages 275–288.
- [17] Paul Tune and Darryl Veitch. Towards optimal sampling for flow size estimation. In *Proceedings of the 8th ACM SIGCOMM conference on Internet measurement*, pages 243–256, 2008.
- [18] M. P. Wand and M. C. Jones. *Kernel smoothing*. Number 60 in Monographs on statistics and applied probability. Chapman & Hall, 1st ed edition.
- [19] Tong Yang, Jie Jiang, Peng Liu, Qun Huang, Junzhi Gong, Yang Zhou, Rui Miao, Xiaoming Li, and Steve Uhlig. Elastic sketch: Adaptive and fast network-wide measurements. In *Proceedings of the 2018 Conference of the ACM Special Interest Group on Data Communication*, pages 561–575. ACM.
- [20] Minlan Yu, Lavanya Jose, and Rui Miao. Software defined traffic measurement with OpenSketch. In *NSDI*, volume 13, pages 29–42.
- [21] Ben Zhang, Xin Jin, Sylvia Ratnasamy, John Wawrzynek, and Edward A. Lee. AWStream: Adaptive wide-area streaming analytics. In *Proceedings of the 2018 Conference of the ACM Special Interest Group on Data Communication*, SIGCOMM '18, pages 236–252. ACM.